D3 DEDUSTER

The Go Fast D3 Series Deduster not only de-dust boards, but this compact machine also de-burrs stringy material off of the sides of boards. Still equipped with the Board Knocker System, this deduster will be an asset to any operation.

SIDE DEBUR BRUSH: A side deburring drum brush is added to remove the stringy material. These stringy materials are usually left-over from a band saw cut. A powered wheel holds the boards tight against the spinning brush, ensuring that most of the stringy material is removed.



STANDARD FEMURES

BOARD KNOCKER SYSTEM



SIDE DE-BURRING BRUSH



SIDE SWEEPING DISC BRUSHES



FEATURES & SPECS

OPTIONS

Machine Options

- Board Width: Can Quote for Specific Widths
- Feed Belt Length: Can Quote Custom Lengths
- 5 HP Single Phase

System Options

- Out-Feed Green Chain
- **Sorting Round Table**
- In-Feed Powered Rollers
- Stack Racks

MACHINE SPECS

Dimensions

- Length: 103" Width: 34"
- Height: 58"
- Feed Belt Height: 27" 36"
- Exit Pinch Roller Height: 34"

- 5HP Electric Motor 208/230/480/3/60 TEFC
- Completely Pre-Wired Motor Started with Start/Stop Buttons and Circuit Overload Protection

Capacities

- Board Width: up to 6"
- Board Thickness: 1/4" 2.5"
- Board Length: Unlimited

Hydraulics

Self Contained 5 GPM System with Variable 0 - 600 Feet Per Minute Feed Speed

POPULAR OPTIONS

TAILING BELT



INFEED ROLLS



