

# DD79 DEDUSTER



The Go Fast Deduster is the solution to sawdust left on boards. Material can be fed by hand or from an inline process into the machines hopper. An adjustable gate allows the rubber feed belt to pull the bottom board forward to the feed wheel and through the top and bottom rotating brushes.

**THE DIFFERENCE:** There are several features that set the Go Fast DeDuster apart from the rest, and it all starts with the brush! Our side sweeping disc brushes sweep sideways, providing cleaner boards than traditional drum brushes. They also do not require an air collection.

**BOARD KNOCKER:** Our famous board knocker system helps meter the boards through the machine one at a time. It breaks frozen and sticky boards apart and prevents 99% of jams!

## STANDARD FEATURES

**BOARD KNOCKER SYSTEM**



**SIDE SWEEPING DISC BRUSHES**



**EVERYTHING POWERED USING JUST (1) 5 HP MOTOR**



# FEATURES & SPECS

## OPTIONS

- 5 HP Single Phase
- Line Shaft: Available Without Power Set to Run Off Line Shaft
- Infeed Rollers
- Outfeed Belt
- Sorting Table
- Stacking Rack

## MACHINE SPECS

### Dimensions

- Length: 79"
- Width: 34"
- Height: 58"
- Feed Belt Height: 27" - 36"
- Exit Pinch Roller Height: 34"

### Capacities

- Board Width: 2" - 6 1/4"
- Board Thickness: 3/8—2.5"
- Board Length: 18" minimum

### Hydraulics

- 10 Gal Reservoir Capacity
- Self Contained 5 GPM System with Variable 0-700 Feet Per Minute Feed Speed

### Power

- 5 HP Electric Motor 208/230/480/3/60 TEFC
- Completely pre-wired motor starter with start/stop buttons and circuit overload protection

## POPULAR OPTIONS

**103 MODEL FOR LONGER MATERIAL**



**TAILING BELT**



**INFEEED ROLLS**



CHOPSAWS  
TRIMSAWS  
FIREWOOD PROCESSING  
RESAWS  
NOTCHERS  
DEDUSTERS  
MATERIAL HANDLING