<u>6 X 6 MASTER RETURN RESAW</u>



The 6 x 6 Master Return Resaw is very similar to our 6 x 8 Master Resaws. This automatic return resaw is equipped with a powered hold-down and an innovative powered belt return, which is self adjusting and offers operators the ability to fine-tune the return belt height and angle to fit your specific mix of products. When setting the sawblade to the desired board thickness, the feed belt conveyor and the return belt are all simultaneously adjusted to maintain optimum height for peak performance

STANDARD FEATURES

AIR TENSION BLADE SYSTEM



ENCLOSED HYDRAULIC SYSTEM





EASY HEIGHT

ADJUSTMENT

FEATURES & SPECS

OPTIONS

Power Options

- 20 HP Electric Motor
- 22 HP Honda Gas Motor
- Line Shaft: Available Without Power Set to Run off Line Shaft
- Single Phase 10 HP

Machine Options

- Conveyor Board Return
- Tailing Belt
- Powered Hold Down
- Soft Starts
- Slave Heads
- Take Away Roller
- Taller Fences
- Air Tensioned Hold Over Plate

System Options

- Cant Sizer
- Green Chain

MACHINE SPECS

Dimensions

- Length: 114"
- Width: 90"
- Height: 48"
- Feed Belt Height: 34"

Power

- 15 HP Electric Motor: 208/230/480/3/60 TEFC
- Completely pre-wired motor starter with start/stop buttons and circuit overload protection

Specifications

- 4" Dust Connection (400 cfm)
- Approx. 1400 lbs
- Uses 15'1" Bands (3/4" to 1-1/4" Wide)
- Top Mounted Powered Hold Down
- Heavy Duty 2-7/16" Arbors & Bearings
- 20" Band Wheels
- Self Contained Hydraulic System with Variable 0-120 Feed Per Minute Feed Speed
- 3" Tall Right Side Fence

Capacities

- Board Width: up to 6"
- Board Thickness: 1/4" 6"
- Board Length: Unlimited

POPULAR OPTIONS

POWERED HOLD DOWN



GAS POWERED





AIR TENSION HOLD OVER

PLATE

